

CP- UNR-7364R8-R**64 Ch. Network Video Recorder****Main Features**

- Upto 64Ch.Camera Connection
- H.264/MJPEG dual codec decoding
- Max 256Mbps incoming bandwidth
- HDMI / VGA simultaneous video output
- Support 8 SATA HDDs up to 32TB, 1 eSATA up to 16TB, 4 USB2.0
- Support RAID 0, RAID 1, RAID 5, RAID 6, RAID 10
- Support Multi-brand network cameras
- ONVIF Version 2.2 conformance
- Mobile Software: CMOB
- CMS Software: KVMS

CP- UNR-7364R8-R

64 Ch. Network Video Recorder

Feature

Processor
 Operating System
 IP Camera Input
 Two-way Talk
 User Interface
 Video Output
 Compression
 Video Resolution
 Video Recording
 Video Display Split
 Motion Detection
 Video Loss
 Camera Blank
 Alarm Input
 Alarm Output
 Smart Phone
 Hard Disk
 Trigger Events
 Recording Mode
 Search Mode
 Playback
 Backup Mode
 Interface Ports
 Record Interval
 Max User Account
 Ethernet
 Protocols
 Power Supply

Specification

Dual-core embedded processor
 Embedded LINUX
 64 channel
 1 channel Input, 1 channel Output, RCA
 GUI
 2 HDMI, 1 VGA, 1TV
 H.264 / MJPEG
 1920 x 1080, 1280 x 1024, 1280 x 720, 1024 x 768
 Max 192 Mbps
 1/4/8/9/16/25/36
 MD Zones: 396(22x18).
 Supports
 Supports
 16 channel
 6 channel
 iPhone, iPad, Android, Windows Phone
 8 SATA ports (8HDDs or 6HDDs+1CD/DVD-RW), up to 32TB, Raid (redundancy), 1 eSATA port (Max 4 SATA HDDs), up to 16TB
 Recording, PTZ, Tour, Alarm, Video Push, Email, FTP, Spot, Buzzer & Screen
 Manual, Schedule(Regular(Continuous), MD, Alarm), Stop
 Time/Date, Alarm, MD & Exact search (accurate to second), Smart search
 Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup selection, Digital zoom
 USB Device / eSATA Device / Internal SATA burner/ Network
 2 HDMI, 1 VGA, 1TV, 4 USB2.0, 1 RS485, 1 RS232, 1 RJ45
 1~120 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec
 128 users
 2 RJ-45 port (10/100M/1000M)
 HTTP, TCP/IP, IPv4/IPv6, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPOE, DDNS, FTP, Alarm Server, ONVIF Version 2.2
 AC 100~240V, 50/60 Hz

 **CP- UNR-7364R8-R****64 Ch. Network Video Recorder****Feature**

Power Consumption

Working Temp

Dimensions

Weight

Specification

75W(without HDD)

-10 ~+55°C / 10~90%RH / 86~106kpa

440mm × 460mm × 89mm

6KG(without HDD)