

HIKVISION TURBO HD BULLET DS-2CE16D0T-IT1



Camera

Image Sensor:	2MP CMOS Image Sensor
Signal System:	PAL/NTSC
Effective Pixels:	1296(H)x732(V)
Min. Illumination:	0.01 Lux @(F1.2,AGC ON), 0 Lux with IR
Shutter Time:	1/25(1/30) s to 1/50,000 s
Lens:	3.6mm (2.8mm, 6mm optional), Angle of View: 70.9°(3.6mm), 92°(2.8mm), 56.7°(6mm)
Lens Mount:	M12
Adjustment Range:	Pan: 0 - 360°, Tilt: 0 - 180°, Rotation: 0 - 360°
Day& Night:	IR cut filter with auto switch
Video Frame Rate:	720p@25fps/720p@30fps
HD Video Output:	1 Analog HD output
Synchronization:	Internal Synchronization
S/N Ratio:	More than 62 dB

General

Operating Conditions:	-40 °C - 60 °C (-40 °F - 140 °F) Humidity 90% or less (non-condensing)
Power Supply:	12 VDC±15%
Power Consumption:	Max. 4W
Weather Proof:	IP66
IR Range:	Up to 40m
Dimension:	86.22x82.05x220.13mm(3.39"x3.23"x8.67")
Weight:	700 g